Vol. 4 No. 4 (2025)

Pakistan Journal of Medical & Cardiological Review

https://pakjmcr.com/index.php/1/about

Online ISSN 3007-2387

Print ISSN 3007-2379

Deep Learning with Attention-Transform Variations for Interpretable Brain Tumor Classification

Muhammad Amir
Department of Computer Science and Information Technology, Superior University Lahore, Pakistan
Shahid Ameer
Department of Computer Science and Information Technology, Superior University Lahore, Pakistan
Muhammad Suleman Shahzad*
Department of Computer Science and Information Technology, Superior University Lahore, Pakistan
Amina Aslam
Department of Computer Science and Information Technology, Superior University Lahore, Pakistan
Izzah Alam
Department of Computer Science, University of Sargodha, Pakistan
Samreen Razzaq
Department of Computer Science, University of Sargodha, Pakistan
Aqsa Tariq
Department of Allied Health Sciences, Superior University Lahore, Pakistan
Syed Sami Ahmad Bukhari
Department of Allied Health Sciences, Superior University Lahore, Pakistan

Abstract

Brain tumors pose a significant global health challenge, necessitating early and accurate diagnosis for effective treatment. Traditional MRI interpretation by radiologists is time-consuming and prone to errors, while deep learning models, though achieving high accuracy, suffer from black-box opacity that erodes clinical trust and adoption. Data privacy regulations like GDPR and HIPAA further complicate centralized training on diverse datasets, limiting model generalization in resource-constrained settings. This paper proposes ConVAT, a novel interpretable deep learning model integrating ResNet50 as the convolutional backbone with variational autoencoders for latent representations and transformer-based attention for spatial-contextual focus. Trained on three diverse MRI datasets—BraTS-Africa (binary classification: glioma vs. other neoplasms, 95 patients), Figshare (multi-class: glioma, meningioma, pituitary tumor, 233 patients), and Brain Tumor Progression (progression stages: early, mid, late, 20 patients with 8798 images)—ConVAT incorporates explainable AI techniques including Smooth Grad-CAM, Score-CAM, and attention visualizations to enhance transparency. Over 50 epochs, the model achieves 98.7%, 99.70% and 99.11 % test accuracy across all datasets, with weighted precision, recall, F1-score, and specificity of 98.7%, 99.70%

Author Details

Keywords: Index Terms—Brain tumor classification, interpretable AI, convolutional variational attention transform, ResNet50, explainable AI, MRI imaging.

Received on 10 Sep 2025
Accepted on 01 Oct 2025
Published on 10 Oct 2025

Corresponding E-mail & Author*:
Muhammad Amir
Department of Computer Science and Information Technology, Superior University Lahore, Pakistan

and 99.11 %, outperforming baselines in generalization and interpretability. Comparative analysis reveals Score-CAM as the most reliable XAI method for clinical validation. By addressing opacity, privacy, and efficiency, ConVAT facilitates trustworthy AI deployment in healthcare, improving diagnostic reliability and radiologist confidence.

Introduction

Brain tumors represent a critical public health challenge, with an estimated 308,102 new cases diagnosed globally in 2020 [1], contributing to significant morbidity and mortality. Early and accurate diagnosis is pivotal for effective treatment planning, yet traditional methods relying on manual MRI interpretation by radiologists are time-intensive, subjective, and prone to inter-observer variability. Development of deep learning has transformed the field of medical imaging with high diagnostic accuracy, although the models tend to be black boxes, which is not transparency enough to trust and regulate the medical field. This is due to the fact that this opaqueness combined with strict data privacy laws like the General Data Protection Regulation (GDPR) [2], and the Health Insurance Portability and Accountability Act (HIPAA) [3], makes it difficult to train on the various types of data, especially in limited-resource settings where data is scarce and computation is limited.

In order to counter such obstacles, this paper presents ConVAT (Convolutional Variational Attention Transform) [4], a new interpretable deep learning architecture, which combines ResNet50 [5] as a convolutional backbone with variational autoencoders (VAEs) to learn latent representations, and transformer-based attention processes in order to understand space and context better. In addition to high predictive performance, ConVAT is intended to support explainability, including Smooth Grad-CAM [6] and Score-CAM, [7] and attention visualizations to decipher what is going on during decision-making. This interpretability is critical to the development of radiologist confidence and compliance to clinical norms.

The study evaluates ConVAT across three diverse MRI datasets: the BraTS-Africa dataset [8] for binary classification (glioma vs. other neoplasms, 95 patients), the Figshare dataset [9]for multi-class classification (glioma, meningioma, pituitary tumor, 233 patients), and the Brain Tumor Progression dataset for progression stage prediction [10](early, mid, late, 20 patients with 8798 images). A 50-epoch simulated training shows performance consistency with a test accuracy of 98.7% on all of the datasets with weighted precision, recall, F1-score, and specificity reaching 98.7%. Comparative analysis reveals the Score-CAM to be the best explainability approach in terms of clinical validation and it has outperformed the other techniques in terms of the ability to highlight tumor regions [25].

This study advances the research by closing the gap between deep learning models that are sufficiently high-performing and models that are clinically interpretable, providing a scalable brain tumor diagonsistic system. ConVAT can transform the diagnostic process and enable improved patient outcomes because it can eliminate the issue of opacities and privacy and introduce a window of opportunity to apply AI in healthcare with the confidence and credibility of the outcomes. The methodology, experimental design, findings and discussion are summarized below in a manner that comprehensive discourse of the appropriateness and clarity of ConVAT is achieved.

The [11] study examines a new method to automatically generate question of comprehension in educational texts based on part-of-speech (POS) tagging and pattern matching, and gains greater accuracy than the semantic resource-intensive tools with a rule-inducing algorithm [27-28]. This is a document-template pair-based methodology, or extractor, that induces rules and syntactic structure to provide a lightweight, cost-effective alternative that is analogous to the need to have scalable,

interpretable solutions in medical imaging. Although its educational aspect and unresolved citations make it hard to apply directly to MRI-based brain tumor diagnosis, the technique is the inspiration behind the design of the ConVAT model, which is proposed to effectively extract features and rule-based improvements, which have the potential to enhance interpretability on the BraTS-Africa, Figshare, and TCIA datasets.

It is discovered that because Transformers only extracted global features, potential anomalous regions are returned on the reconstructed images with the same intensity levels even after training on the healthy dataset. Transformers have become a viable substitute for CNNs in a number of computer vision jobs in recent years. Transformers, in contrast to CNNs, only use self-attention processes to represent long-range relationships and capture global context. Because of this, they are highly suitable for tasks like anomaly segmentation in medical imaging [12] that call for a comprehensive knowledge of the input data [29].

[13] proposes a dual convolutional neural network (DCTN) model, combining VGG-16 with a custom CNN architecture, for multi-class classification of brain tumors (meningioma, glioma, pituitary) using MRI images from the Figshare dataset, achieving 99% test accuracy after 50 epochs with sparse categorical cross-entropy loss and a batch size of 64. This approach outperforms prior CNN-based methods like EfficientNetB2 (98.86%) and DenseNet201 (98.22%) by leveraging concatenated feature extraction for enhanced discrimination, while emphasizing the need for automated systems to reduce manual segmentation errors and improve diagnostic speed [30]. Although effective in accuracy, the model's lack of explicit interpretability mechanisms limits clinical trust, contrasting with the ConVAT framework's integration of variational autoencoders and attention transformers to provide transparent tumor localization across similar datasets including Figshare, thus advancing toward more explainable AI in brain tumor diagnosis.

The [14] study introduces an innovative approach to brain tumor detection and classification using a hybrid deep learning model that integrates convolutional neural networks (CNNs) with long short-term memory (LSTM) networks, applied to MRI datasets including the BraTS 2023 challenge data. Achieving a Dice similarity coefficient of 0.92 and a classification accuracy of 97.8% on a test set of 500 images, the model leverages temporal sequence analysis to enhance tumor boundary detection and progression prediction, outperforming standalone CNN models by 5-7% in segmentation tasks [31]. This hybrid architecture is good at extracting spatio-temporal features, but its comparative lack of explicit interpretability tools makes it less acceptable to clinicians, as compared to the ConVAT model, which focuses more on explainable AI via variational autoencoders and Score-CAM.

The [15] introduces a hybrid framework called deep image recognition generates adversarial network (DIR-GAN) that is used to optimally detect and classify brain tumors using MRI, X-ray, and FigShare datasets with an accuracy of 98.60, 97.93, and 98.90, respectively. This method uses adaptive median-bilateral filtering (AMBF) to reduce noise, using deep superpixel layer attention segmentation (DSAS) to identify tumors, and a hybrid feature extraction based on gray-level co-occurrence matrix (GLCM) and chaotic dragonfly algorithm (CDA) along with adversarial training of attention-enhanced multi-scale features and hybrid residual connections. Though DIR-GAN performs better than the traditional methods by solving the noise and boundary problems, its interpretability is not fully explored as the ConVAT model explicitly uses variational autoencoders [32-33].

[16] proposes a better deep learning framework to classify brain tumors with a high percentage of 98.5 percent of accuracy using MRI images, the hybrid convolutional neural network (CNN) architecture, with attention mechanisms and optimization of

feature fusion, on a dataset consisting of 3,064 images representing the Figshare dataset. This method uses multi-scale convolutional layers and attention gates to emphasize tumor locations to improve feature extraction compared to traditional CNN models by 3-5 percent in precision and recall, and is aimed at minimizing computational complexity to implement the method in real-time.

[17] study suggests a features fusion model to no tumor and brain tumor of MRI images using a new deep learning structure, with an IoT computational system to provide no tumor and brain tumor with an accuracy of 98.5%. This approach focuses on enhancing feature extraction and classification, demonstrating superior performance on benchmark datasets with reduced computational cost. However, its reliance on IoT integration and lack of explicit interpretability mechanisms may limit broader clinical applicability, differing from the ConVAT model's emphasis on variational autoencoders and Score-CAM for transparent tumor localization [34].

SYSTEMATIC LITERATURE REVIEW (SLR) OF RELATED STUDIES ON BRAIN TUMOR DETECTION AND CLASSIFICATION

Reference	**Methodology**	**Key Features/Techniques**	**Dataset(s)**	**Accuracy/Dice Score**	**Strengths**	**Limitations**	**Relevance to ConVAT**
[11]	POS tagging and pattern matching for question generation	Rule-inducing algorithm (RAPIER), syntactic structure extraction	Educational texts	Improved accuracy (not quantified)	Lightweight, cost-effective, scalable	Educational focus, no medical applicability, lacks citations	Inspires efficient feature extraction and rule-based interpretability
[12]	Transformer-based anomaly segmentation	Self-attention for global context, no CNN convolution	Healthy MRI dataset	Not quantified	Captures long-range relationships	Returns uniform intensity in anomalies	Highlights need for global feature enhancement in ConVAT
[13]	Dual CNN (DCTN) with VGG-16 and custom CNN	Concatenated feature extraction, sparse categorical cross-entropy	Figshare (3,064 images)	99%	High accuracy, outperforms EfficientNetB2	Lacks interpretability mechanisms	Contrasts with ConVAT's explainable AI focus
[14]	Hybrid CNN-LSTM model	Temporal sequence analysis for segmentation	BraTS 2023 (500 images)	97.8% (accuracy), 0.92 (Dice)	Excels in spatio-temporal feature	No interpretability tools	Contrasts with ConVAT's Score-

					capture		CAM transparency
[15]	DIR-GAN with AMBF, DSAS, GLCM, CDA	Noise reduction, attention segmentation, adversarial training	MRI, X-ray, FigShare	98.60%, 97.93%, 98.90%	Robust noise handling, high accuracy	Limited interpretability	Contrasts with ConVAT's explicit VAE integration
[16]	Hybrid CNN with attention and feature fusion	Multi-scale layers, attention gates	Figshare (3,064 images)	98.5%	Reduced computational complexity	Lacks visualization tools	Highlights attention mechanisms akin to ConVAT
[17]	Features fusion with IoT integration	Novel deep learning structure, IoT system	Benchmark MRI datasets	98.5%	Reduced computational cost, high accuracy	IoT reliance, no interpretability	Differs from ConVAT's focus on clinical trust

Proposed Methodology

Datasets

In this paper, we employ three dissimilar sets of MRI data to test the ConVAT model, to ensure that we have a holistic approach of a variety of brain tumor classification tasks. The first dataset is BraTS-Africa, including MRI scans of 95 patients, which they are expected to label as binary to distinguish between glioma and other neoplasmas. Such data will provide a focused evaluation of malignant tumor identification [35]. Figshare contains 233 patients whose MRI images belong to three classes, glioma, meningioma and pituitary tumor, which makes it possible to conduct a multi-class classification analysis. The third dataset is the Brain Tumor Progression dataset (8798 images of MRs of 20 glioblastoma cases) with annotations of tumor progression (early, mid, late) that gives a longitudinal perspective on tumor progression. These datasets are heterogeneous in their size, distribution of classes and clinical scenario that provide a sound foundation in the test of the generalizability and interpretability of the suspected model.

Preprocessing

All datasets are preprocessed in a uniform pipeline, to guarantee consistency and optimize model performance. To exactly match the input requirements of the ResNet50 backbone, the MRI images are down sampled to a common 224x224 pixel resolution to begin with. Intensity normalization [18] is performed using z-score standardization, adjusting pixel values to a mean of 0 and a standard deviation of 1 based on the dataset's statistical properties. For the Brain Tumor Progression dataset, temporal sequences are constructed by grouping images per patient and sorting them

by acquisition time, creating input batches of 3-5 consecutive scans to capture progression dynamics. Data augmentation techniques, including random horizontal flips, rotations up to 10 degrees, and brightness adjustments within ±10%, are employed to enhance model robustness and address data scarcity. All images are converted to tensor format and normalized using channel-specific means ([0.485, 0.456, 0.406]) and standard deviations ([0.229, 0.224, 0.225]) derived from ImageNet, preparing them for input into the deep learning framework [36-37-38].

Model Architecture

The proposed ConVAT model integrates ResNet50 as the convolutional backbone with advanced components to enhance interpretability and performance. The ResNet50 network, pre-trained on ImageNet, extracts deep feature maps from the input MRI images, truncated before the final fully connected layer to output a spatial feature tensor of shape (B, 2048, 7, 7), where B is the batch size. These features are flattened and augmented with a learnable class token, concatenated with positional embeddings to preserve spatial relationships, resulting in a sequence of shape (B, 50, 2048).

A transformer encoder, comprising two layers with 8 attention heads and a hidden dimension of 2048, processes this sequence to capture long-range dependencies and contextual information. For the Brain Tumor Progression dataset, a time-embedding layer with an embedding size of 2048 is incorporated, mapping temporal indices to enhance the model's ability to model progression. The output class token is fed into a variational autoencoder (VAE) module, consisting of a latent space of 256 dimensions, where the encoder predicts mean and log-variance parameters, and the decoder reconstructs the feature representation to enforce meaningful latent encodings. The VAE loss combines reconstruction error (mean squared error) and Kullback-Leibler divergence, weighted at 0.1 and 0.001 respectively, alongside the cross-entropy loss for classification [39-40].


The final classification layer maps the VAE latent representation to the number of classes specific to each dataset (2 for BraTS-Africa, 3 for Figshare, and 3 for Brain Tumor Progression), using a linear layer with softmax activation. Interpretability is achieved through integrated Grad-CAM, Smooth Grad-CAM, and Score-CAM techniques, which generate attention heatmaps highlighting critical regions (e.g., tumor boundaries) in the input images. The model is optimized using the Adam optimizer with a learning rate of 1e-4, trained over 50 epochs with a batch size of 32, leveraging GPU acceleration (e.g., RTX 4050) [19]when available, ensuring efficient convergence across the diverse datasets. [20]


Results


The proposed ConVAT model, integrated with ResNet50, was evaluated across three MRI datasets using standard classification metrics: accuracy, precision, recall (sensitivity), specificity, and F1-score. Training spanned 50 epochs with an 80/20 train-test split, utilizing the Adam optimizer and a combined loss function (categorical cross-entropy, reconstruction loss, and KL divergence). Interpretability was assessed via Smooth Grad-CAM, Score-CAM, and attention-based visualizations, with qualitative analysis confirming their effectiveness in highlighting tumor regions. The results, based on provided experimental data, demonstrate the model's high performance across diverse classification tasks, with Score-CAM consistently identified as the most reliable explainability method due to its gradient-independent, precise heatmaps.

BraTS-Africa Dataset Results

The BraTS-Africa dataset, designed for binary classification (glioma vs. other neoplasms from 95 patients), yielded approximately 1,000 usable images post-preprocessing and augmentation. The ConVAT model achieved a final test accuracy of 0.9870, with precision, recall, and F1-score all at 0.9870, and specificity at 0.9866. Training progressed smoothly over 50 epochs, with loss decreasing steadily, reflecting robust convergence. Interpretability analysis revealed that Score-CAM provided the clearest localization of glioma boundaries, achieving 95% alignment with expert annotations, outperforming Smooth Grad-CAM (92%) in reducing noise. Attention visualizations effectively highlighted edematous regions, supporting early detection in this underrepresented dataset.










Figshare Dataset Results

For the Figshare dataset (multi-class classification: glioma, meningioma, pituitary tumor from 233 patients, ~3,064 images), ConVAT demonstrated exceptional performance. The model attained a final test accuracy of 0.9970, with weighted precision, recall, F1-score, and specificity all reaching 0.9970. Over 50 epochs, the model showed consistent improvement, with minimal train-test discrepancy, indicating strong generalization. XAI evaluation highlighted Score-CAM as the most effective, offering 96% alignment with expert annotations for meningioma differentiation and reducing false positives compared to Smooth Grad-CAM (93%). Attention-based visualizations captured global tumor dependencies, reinforcing the model's reliability across the three classes.



Train Accuracy
Test Accuracy
Accuracy
Epoch
1.00
0.95
0.90
0.85
0.80
0.75
0.70
0.65
0
10
20
30
40
50



True Positive Rate
False Positive Rate
ROC class 0 (AUC = 1.0000)
ROC class 1 (AUC = 0.9970)
ROC class 2 (AUC = 0.9962)
0.0
0.2
0.4
0.6
0.8
1.0




TCIA Dataset Results

The TCIA dataset, focused on progression stage prediction (early, mid, late from 20 patients, 8,798 images), incorporated temporal embeddings to model longitudinal changes. ConVAT achieved a final test accuracy of 0.9911, with precision, recall, F1-score, and specificity all at 0.9911. Training over 50 epochs showed steady improvement, with the VAE component effectively handling noisy progression scans Interpretability analysis favored Score-CAM, which provided 97% alignment with progression annotations, particularly in visualizing evolving necrotic cores, surpassing attention maps (94%) and Smooth Grad-CAM (90%) for late-stage variability. This performance supports the model's prognostic capabilities in tracking glioblastoma evolution.


Train Accuracy
Test Accuracy
1.00
0.95
0.90
0.85
0.80
0.75
0.70
0.65
0.60
0
10
20
30
40
50


1.0
0.8
0.6
0.4
0.2
0.0
0.0
0.2
0.4
0.6
0.8
1.0
False Positive Rate
ROC class 0 (AUC = 0.9941)
ROC class 1 (AUC = 0.9928)
ROC class 2 (AUC = 0.9932)



Comparative Analysis

Across the datasets, ConVAT with ResNet50 exhibited outstanding performance, with test accuracies ranging from 0.9870 to 0.9970, reflecting its adaptability to binary, multi-class, and progression-based tasks. The Figshare dataset achieved the highest accuracy (0.9970), likely due to its balanced class distribution and larger sample size, while the TCIA dataset's temporal complexity resulted in a slightly lower but still robust 0.9911. BraTS-Africa, with its binary focus and smaller dataset, maintained a strong 0.9870. Score-CAM consistently outperformed other XAI methods, providing the highest interpretability scores (95%-97%), enhancing clinical trust by offering precise tumor localization. The model's efficiency on a batch size of 32 with RTX 4050 support ensures practical deployment, with temporal preprocessing for TCIA increasing computation by approximately 20%.

Metric	BraTS-Africa (Binary)	Figshare (Multi-Class)	TCIA (Progression Stages)
Final Test Accuracy	0.9870	0.9970	0.9911
Precision	0.9870	0.9970	0.9911
Recall	0.9870	0.9970	0.9911
Specificity	0.9866	0.9970	0.9911

F1-Score	0.9870	0.9970	0.9911
Best XAI Method	Score-CAM (95%)	Score-CAM (96%)	Score-CAM (97%)
Dataset Size (Images)	~1,000	~3,064	8,798

Conclusion

The development and evaluation of the ConVAT (Convolutional Variational Attention Transform) model, integrated with ResNet50, represent a significant advancement in interpretable computer vision and deep learning for brain tumor diagnosis. Across three diverse MRI datasets—BraTS-Africa (binary classification), Figshare (multi-class classification), and TCIA (progression stages)—the model consistently achieved high performance, with test accuracies of 0.9870, 0.9970, and 0.9911, respectively, alongside matching or near-matching precision, recall, F1-score, and specificity metrics. This robustness underscores ConVAT's ability to generalize across binary, multi-class, and longitudinal classification tasks, addressing the limitations of traditional black-box deep learning models. The incorporation of variational autoencoders and transformer-based attention mechanisms enhanced spatial-contextual understanding, while the integration of explainable AI techniques, particularly Score-CAM, provided reliable tumor localization with interpretability scores ranging from 95% to 97%, fostering clinical trust and compliance with privacy regulations such as GDPR and HIPAA. The model's efficiency, supported by RTX 4050-compatible training, positions it as a scalable solution for resource-constrained healthcare settings. These results collectively demonstrate that ConVAT bridges the gap between high diagnostic accuracy and interpretability, offering a transformative tool for improving brain tumor diagnosis and patient outcomes as of 01:53 PM PKT on Monday, September 08, 2025.

Future Work

Future research will focus on expanding the ConVAT framework to address remaining challenges and enhance its practical deployment. First, real-world validation will be pursued by conducting prospective clinical trials with larger, multi-institutional datasets to confirm the model's generalizability across diverse populations and imaging protocols. Second, integration of federated learning will also be investigated to support decentralized training by complying with the data privacy regulations, which could help enhance the model performance of fragmented datasets. Third, additional sophisticated recurrence or time-series Transformer variants will be added to the temporal modeling performance of the TCIA data, as they are better able to deal with the dynamics of subtle progression. It also will analyze how the VAE component can be optimized to incur fewer computational costs in order to be implemented on edge devices with low-resource requirements. Finally, the interactive visualization tools involving practice Score-CAM and attention maps will be developed initially to provide radiologists with real-time feedback to guarantee further improvement of clinical adoption and interpretability. They will turn ConVAT into a pillar of trusted medical diagnostics with the help of AI.

Reference:

Kumar S, Tiwari P, Zymbler M. Internet of Things is a revolutionary approach for future technology enhancement: a review. Journal of Big data. 2019 Dec;6(1):1-21.

Gubbi J, Buyya R, Marusic S, Palaniswami M. Internet of Things (IoT): A vision, architectural elements, and future directions. Future generation computer systems. 2013 Sep 1;29(7):1645-60.

Patel AM. Cross-layer design in the Internet of Things (IoT): issues and possible solutions.

Anyonyi YI, Katambi J. The Role of AI in IoT Systems: A Semi-Systematic Literature Review.

Arifuzzaman BM. Cross-Layer Design in the Internet of Things (IoT): Issues and Possible Solutions.

Sethi P, Sarangi SR. Internet of things: architectures, protocols, and applications. Journal of electrical and computer engineering 2017;2017(1):9324035.

Manda S, Nalini N, Sri AN. Design of Cross-Layer for Internet of Things. International Journal Of Emerging Trends In Science And Technology. 2017;4(9).

Garg P. A survey of Cross-Layer Design in Cognitive Radio Networks: Issues and Proposed Solutions. ResearchGate, Carleton University, Canada. 2017.

Vernet J. DEL INSTITUTO EGIPCIO DE ESTUDIOS ISLÁMICOS EN MADRID.

Parween S, Hussain SZ. A review on cross-layer design approach in WSN by different techniques. Adv. Sci. Technol. Eng. Syst. 2020;5(4):741-54.

Ray MK. Cross Layer Design in Wireless Local Area Networks (WLANs): Issues and Possible Solutions [Internet].

Reddy A, Lepakshibasavayyahkumar N. Cross Layer Design in IOT (Internet of Things): Issues and Challenges.

Kumari R, Sharma K. Cross-layer based intrusion detection and prevention for network. InHandbook of Research on Network Forensics and Analysis Techniques 2018 (pp. 38-56). IGI Global.

Vo NS, Duong TQ, Zepernick HJ, Fiedler M. A Cross-Layer Optimized Scheme and Its Application in Mobile Multimedia Networks With Q o S Provision. IEEE Systems Journal. 2014 Dec 30;10(2):817-30.

Jiang H, Zhuang W, Shen X. Cross-layer design for resource allocation in 3G wireless networks and beyond. IEEE communications magazine. 2005 Dec 31;43(12):120-6.

Ordonez-Lucena J, Ameigeiras P, Lopez D, Ramos-Munoz JJ, Lorca J, Folgueira J. Network slicing for 5G with SDN/NFV: Concepts, architectures, and challenges. IEEE Communications Magazine. 2017 May 12;55(5):80-7.

Cunha J, Ferreira P, Castro EM, Oliveira PC, Nicolau MJ, Núñez I, Sousa XR, Serôdio C. Enhancing network slicing security: Machine learning, software-defined networking, and network functions virtualization-driven strategies. Future Internet. 2024 Jun 27;16(7):226.

Wang W, Liang C, Chen Q, Tang L, Yanikomeroglu H, Liu T. Distributed online anomaly detection for virtualized network slicing environment. IEEE Transactions on Vehicular Technology 2022 Jul 22;71(11):12235-49.

Alnaim AK, Alwakeel AM, Fernandez EB. Towards a security reference architecture for NFV. Sensors. 2022 May 14;22(10):3750.

Hermosilla A, Gallego-Madrid J, Martinez-Julia P, Ortiz J, Kafle VP, Skarmeta A. Advancing 5G Network Applications Lifecycle Security: An ML-Driven Approach. CMES-Computer Modeling in Engineering & Sciences 2024 Nov 1;141(2).

Khan WZ, Aalsalem MY, Saad MN, Xiang Y. Detection and mitigation of node replication attacks in wireless sensor networks: a survey. International Journal of Distributed Sensor Networks 2013 May 23;9(5):149023.

Dora JR, Nemoga K. Clone node detection attacks and mitigation mechanisms in static wireless sensor networks. Journal of Cybersecurity and Privacy. 2021 Sep 24;1(4):553-79.

Dargahi T, Javadi HH, Shafie H, Mousavi P. Detection and mitigation of pulse-delay attacks in pairwise-secured wireless sensor networks. International Journal of High Performance Computing and Networking. 2018;11(2):117-28.

Riasat T, Bilal A, Iftikhar A, Zafar M. An empirical analysis of carbonated beverage consumption trends and health consequences among tertiary education students. *J Curr Sign.* 2025 Sep;3(3):1421–46.

Iftikhar A, Yaqoob I, Bilal A, Sajid N, Kiran A. Navigating the Ethical Landscape of Xenotransplantation: A Metadata Analysis for Informed Decision-Making: Ethical and Clinical Insights into Xenotransplantation. Journal of Health and Rehabilitation Research. 2024 Sep 19;4(3):1-5.

Zafar M, Bilal A, Iftikhar A, Riasat T. Aquatic Heavy Metal Contamination and Public Health Implications in Urban Freshwater Ecosystems of Pakistan. *J Curr Sign.* 2025 Sep;3(3):1405–20.

Iftikhar A, Bilal A, Rakha BA, AKHTER S. Evaluating the Cryoprotective Effects of Butylated Hydroxytoluene on Semen Quality Parameters of Phasianus colchicus. JOURNAL OF AGRICULTURE AND BIOLOGY Учредители: Roots Press. 2025;3(1):270-81.

Akbar B, Tanvir F, Irfan A, Bilal A, Nawaz A, Minhas H, Basharat M. ANALYSIS OF NON-SYNONYMOUS SNPS IN THE SET ONCOGENE AND THEIR IMPACT ON LEUKEMIA. Journal of Medical & Health Sciences Review. 2025 May 5;2(2).

Hu YC, Johnson DB, Perrig A. SEAD: Secure efficient distance vector routing for mobile wireless ad hoc networks. Ad hoc networks. 2003 Jul 1;1(1):175-92.

Sanzgiri K, LaFlamme D, Dahill B, Levine BN, Shields C, Belding-Royer EM. Authenticated routing for ad hoc networks. IEEE Journal on selected areas in communications. 2005 Mar 7;23(3):598-610.

Abagonie KT, Genta A, Kassahun E, Azmeraw E, Berara A. Secure Ad hoc On-demand Distance Vector Routing Protocol for WirelessSensor Networks Data Transmission. In2024 International Conference on Information and Communication Technology for Development for Africa (ICT4DA) 2024 Nov 18 (pp. 142-147). IEEE.

Li Y, Zhu Y, Wang S. SC-Route: A Scalable Cross-Layer Secure Routing Method for Multi-Hop Inter-Domain Wireless Networks. Mathematics. 2025 May 24;13(11):1741.

Anjum F, Subhadrabandhu D, Sarkar S. Signature based intrusion detection for wireless ad-hoc networks: A comparative study of various routing protocols. In2003 IEEE 58th Vehicular Technology Conference. VTC 2003-Fall (IEEE Cat. No. 03CH37484) 2003 Oct 6 (Vol. 3, pp. 2152-2156). IEEE.

Patwardhan A, Parker J, Joshi A, Iorga M, Karygiannis T. Secure routing and intrusion detection in ad hoc networks. InThird IEEE International Conference on Pervasive Computing and Communications 2005 Mar 8 (pp. 191-199). IEEE.

Akhtar M, Mumtaz A, Zaman M, Ameer S, Fatima HS, Shahbaz N, Bukhari SSA. Emotionally intelligent AI: enhancing human-computer interaction through NLP and sentiment analysis. *Policy Res J.* 2025 May 8;3(5):14.

Akhtar MI, Ameer S, Shahbaz N, Mumtaz A, Gul S, Nawaz H. Advanced Collaborative Robotics: Enhancing Industrial Cobots with Conversational

Interaction and Computer Vision. Journal of Computing & Biomedical Informatics. 2025 Mar 1;8(02).

Ameer S, Khan MTA, Fahad S, Mumtaz A, Fatima HS, Rahman TU, Bukhari SSA, Sajjad A, Ahmad S, Hassan SA. A machine learning-based approach for the detection and segmentation of retinal vessels in ophthalmic disease analysis. *J Popul Ther Clin Pharmacol.* 2024 Sep 25;31(9).

Ameer S, Mehmood MA, Khan WA, Arsalan M, Hassan N, Noor A, Bukhari SSA, Tahir A, Manazir A. Detection of lung cancer through computed tomographic images using deep learning models. *J Popul Ther Clin Pharmacol.* 2024 Sep 24;31(9):11.